



A/B Expanded PTFE Tape

COMPOSITION 100% P.T.F.E. TEFLON® 65/N.

TECHNICAL FEATURES

CHEMICALLY INERT.

DENSITY: 0,55 gr/cm³.

It is inodorous and tasteless till temperatures of +270°C.

Soft and e flexible guarantees a perfect tightness on irregular or defective areas.

RESISTANCES

PRESSURE: 210bar.

TEMPERATURE: -200°C +280°C, up to 315°C.

CHEMISTRY: PH 0-14; it is resistant to all chemical products and solvents, exception for alkaline materials in particular conditions (as Du Pont literature).

PROPERTIES

INSURES a perfect tightness of long life on flanges of poms and pressers , of industrial and chemical equipments, of pipes and steam's conduits, hydrocarbons, weapon fluids in general and oxygen.

Use on tanks of pyroceram and synthetic resin in chemical and food industry.

INSTRUCTIONS

Degrease, clean and dry the areas to connect; remove the protecting strip from the adhesive surface and position the gasket; conclude the operation with the intercrossed superimposition of the extremity or connectings the same ones with oblique cut. Proceed with the gradual and intercrossed clamping of the bolts. If necessary regulate the tightening on the exercise temperature. In the presence of fragile areas or reduced forces of tightening, the cut oblique connection is preferable.

CERTIFIED PRODUCT TÜV.

ACCORDING TO THE REGULATIONS OF FDA and WRC.